

09-18-00

A

Please type a plus sign (+) inside this box → ☐PTO/SB/05 (12/97) (modified)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 425282000100

Total Pages 21

First Named Inventor or Application Identifier

Frank R. GEORGE, Robert T. BRYANT, Michael F. DALY, Arthur A. LOYA and
Mary C. RITZ


Express Mail Label No. EL352557693US

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Express Mail Label No.: EL352557693US

Date of Deposit: September 14, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.


Chase TrombellaUS PTO
09/14/00
09/14/00**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Transmittal Form [Total Pages]
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets]
4. ☒ Oath or Declaration (unsigned) [Total Pages]
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in
the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the
oath or declaration is supplied under Box 4b, is considered as being
part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐


17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No:
18. CORRESPONDENCE ADDRESSPaul J. Riley
Registration No. 38,596Morrison & Foerster LLP
425 Market Street
San Francisco, California 94105-2482
Telephone: (415) 268-6139
Facsimile: (415) 268-7522

The filing fee has been calculated as follows:

FOR	NUMBER FILED	NUMBER EXTRA	RATE	CALCULATIONS
TOTAL CLAIMS	20 - 20 =	-0-	x \$18.00	\$0.00
INDEPENDENT CLAIMS	3 - 3 =	-0-	x \$78.00	\$0.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$0.00
			BASIC FEE	\$0.00
			TOTAL OF ABOVE CALCULATIONS =	\$0.00
Reduction by 1/2 for filing by small entity (Note 37 C.F.R. §§ 1.9, 1.27, 1.28). If applicable, verified statement must be attached.				\$0.00
			TOTAL =	\$0.00

Dated: September 14, 2000

Respectfully submitted,

By: 
Paul J. Riley
Registration No. 38,596

Morrison & Foerster LLP
425 Market Street
San Francisco, California 94105-2482
Telephone: (415) 268-6139
Facsimile: (415) 268-7522

COVER FOR ELECTROMAGNETIC TREATMENT APPLICATOR

Cross-Reference to Related Applications

5 This application claims the benefit of provisional application no. 60/154,435, filed September 17, 1999.

Field of the Invention

10 The present invention relates to electromagnetic treatment devices, and more particularly to an apparatus for covering an electromagnetic energy treatment applicator which protects the applicator from biohazards and provides selective radio frequency (RF) shielding.

Background of the Invention

15 Electrotherapy includes various means of applying an electric or electromagnetic field to a wound area to facilitate growth and proliferation of new tissue, i.e., healing. In an earlier patent application filed by the present inventors, an electromagnetic treatment device is disclosed. The device includes a pulsed electromagnetic energy generator, a power level controller and one or more applicators. Each applicator is a pad comprising one or more
20 etched copper printed circuits laminated between insulating sheets of material having high dielectric properties. Sensing units, including an electromagnetic signal strength detector and an applicator-to-patient proximity detector, are incorporated in each applicator and are in communication with the power level controller to provide for direct monitoring of the electromagnetic energy field and precise control of the treatment dosage. The applicators,

which are constructed in a variety of shapes and sizes to best match the wound size and area on the patient, are placed over, under or around a bandaged wound site. Since the applicators are not disposable items, needs exist for apparatus which prevent cross-contamination between patients.

5 In addition, electromagnetic treatment applicators remain in direct contact with the wound site during treatment. Thus, the patient, and possibly the health care providers, are potentially exposed to the emitted radiation. Needs exist for apparatus which limit undesired exposure of the patient and health care provider to the treatment radiation.

Existing covers for radiation shielding and medical applications are unacceptable for use with electromagnetic treatment applicators, such as the one described above. Typical covers for use in medical applications are disclosed in U.S. Patent Nos. 3,942,023, 4,605,124 and 4,715,366. Examples of other devices which provide radiation shielding are disclosed in U.S. Patent Nos. 5,336,896 and 5,523,581. Needs exist for covers for electromagnetic treatment applicators which are cost effective, disposable and easy to use.

15 Citation of the above documents is not intended as an admission that any of the foregoing is pertinent prior art. All statements as to the date or representation as to the contents of these documents is based on the information available to the applicants and does not constitute any admission as to the correctness of the dates or contents of these documents.

Further, all documents referred to throughout this application are incorporated in their

20 entirety by reference herein.

Summary of the Invention

It should be apparent that there exists a need for facilitating the safe and effective treatment of patients with electromagnetic energy. It is therefore a primary object of the present invention to fulfill that need by providing a cost effective, easy to use, disposable
 5 cover for use with an electromagnetic energy treatment applicator. The present cover is easy to affix to the treatment applicator, assists in easy application of the applicator to the patient, promotes the transmission of RF energy waves to the patient while blocking the propagation of those waves in any other direction, and provides biohazard shielding for protecting against the transmission of diseases between patients. Further, the cover is configured in a manner which integrates the electromagnetic properties of the cover into the circuitry for the treatment applicator, such that the applicator is not functional in the absence of the cover, thereby providing additional safeguards that the intended treatment is safe and efficacious.

More particularly, the present invention is a disposable cover for devices that are used for therapeutically treating humans with dosages of electromagnetic energy. The cover
 15 includes RF shielding material oriented toward the backside of the cover, opposite the treatment area. At least a portion of the cover which faces the treatment area is constructed solely from non-shielding material. Securing means, such as adhesive strips, ZIP-LOCK®, or other interlocking edges, are provided for securing the applicator inside the cover and closing off any leaks. The cover also includes portions which wrap around the cord leading from the
 20 applicator to the generating unit.

In use, an electromagnetic treatment applicator is inserted into the present cover and positioned over the area to be treated, with the non-shielding, or “window”, portion of the

cover overlying the treatment area. In one embodiment, the dimensions of the “window” are formed by removing selected strips from the outer surface of the cover. Once assembled, the applicator/cover combination forms a closely matched and tuned network for effecting a highly efficient RF output. When activated, the generated electromagnetic energy only exits the cover through the opening or “window”, thereby preventing exposure of the patient or caregiver to potentially harmful radiation.

The present invention has immediate commercial market potential in the field of chronic wound healing. Beyond that immediate market, the present invention may also be utilized in other treatment fields where increasing the rate of growth and proliferation of human or other living cells is essential, including the treatment of burns and surgically implanted skin or soft tissue grafts, sports and rehabilitation medicine, post surgical repair, and neuronal/brain/spinal injury repair and regeneration. In addition to the medical treatment of soft tissue, the present invention has applications in the field of laboratory growth/manufacturing of skin grafts to be sold and used in various surgical settings, veterinary medicine and related fields.

These and further and other objects and features of the invention are apparent in the disclosure, which includes the above and ongoing written specification, with the drawings.

Brief Description of the Drawings

FIG. 1 is a plan view of the disposable cover;

FIG. 2 is a block diagram showing how the cover is configured to integrate its electromagnetic properties into the circuitry of the applicator; and

FIG. 3 is a plan view of the disposable cover with mating interlocking structures.

Detailed Description of the Invention

Referring now to the drawings, where like elements are designated by like reference numerals throughout, FIG. 1 shows an apparatus, more fully described below, for covering an electromagnetic energy treatment applicator. Apparatus 1 includes a front sheet 3 and a back sheet 5. Edges of the sheets 3, 5 are sealed or otherwise connected to form a pouch-like structure with an open end 7 for receiving an applicator (not shown). In alternative embodiments, the apparatus 1 is made from a single sheet, which is folded and sealed such that it has an open end 7. The front sheet 3 (which faces the treatment area) is preferably made, at least partially, of a non-shielding material, such as transparent polyethylene. The back sheet 5 (which faces opposite, or away from, the treatment area) is preferably constructed entirely from shielding material, such as metallized polyethylene, thereby ensuring the blockage of unintended RF transmissions in nontreatment directions. One or more light adhesive strips are located along the outer surface of the front sheet 3 for affixing the cover 1 to a bandage. Preferably, the front sheet 3 of the cover 1 has a patch of adhesive at its center for securing the applicator over the treatment area. The selected adhesive is of low bonding force enabling easy separation from the mating surface.

As shown in FIG. 1, a tab portion 11 extends from the front sheet 3. After the applicator is inserted in the cover 1 through its open end 7, tab portion 11 is folded over such that it overlies a section of the outer surface 13 of the back sheet 5. In one embodiment, an adhesive strip 15 is provided along the outer surface 13 of the back sheet 5 for securing the

tab portion 11 in its folded position. In another embodiment, tab portion 11 has a permanent adhesive strip which preferably runs the length of the unsealed end. It should be understood that other attachment means for securing the tab portion 11 in its folded position are contemplated by the present invention. Preferably, tab portion 11 includes a semi-circular notch 17 or other similar opening or spacing which allows a coaxial cable to protrude therethrough when the cover 1 is sealed. Tab portion 11 further includes perforations 19, preferably provided along the length of the tab portion 11, for enabling easy removal. It should also be understood that, in yet another embodiment, tab portion 11 consists of a ZIP-LOCK® strip or other interlocking means to connect it to a second tab portion extending along the top of front sheet 3. (FIG. 3)

For additional biohazard protection, the tab portion 11 is extended, thereby allowing the tab portion 11 to be wrapped around the cable. In such embodiments, no notch is required. Rather, the extended tab portion 11 is wrapped around the cable and secured thereto with adhesive located along a surface of the tab portion. The tab portion is also secured to the back sheet 5 to seal off entry to the interior of the cover 1 where the applicator is located.

It should be understood that the tab portion 11 can extend from the back sheet 5, as opposed to the front sheet 3, or from both the back sheet 5 and the front sheet 3 without departing from the scope of the present invention. Other means for sealing off the open end of the cover 1, including, but not limited to, mating tabs, ZIP-LOCK® strips, or other fastening means, are also contemplated by the present invention.

In an alternative preferred embodiment, shown in FIG. 3, tab portions extend from both the front sheet 3 and the back sheet 5. Mating interlocking means 12, such as ZIP-

LOCK® strips, are located along each tab portion 11.

In its preferred form, the cover 1 is rectangular in shape and approximately 10 inches by 12 inches in size. The thickness of the cover 1 is approximately 1/100 of an inch. At least the outer surface of the cover 1 is water proof and bacterial resistant, and is designed to be placed directly on the patient or on top of any standard dressings used over the area to be treated.

As described earlier, the cover 1 is composed of a combination of two types of materials - one selected for its properties of resistance to transmission of RF waves and one selected for its ability to be mechanically joined to the first material. Both materials are preferably also good barriers to moisture absorption, thereby preventing biohazards from coming in contact with the applicator surfaces. The RF shielding material prevents emission from the applicator in any direction other than that to be focused at the wound site. The shielding enables the use of the electromagnetic treatment device while being compliant with standards for transmission of radio frequency and other forms of electromagnetic energy.

In its simplest form, the front sheet 3 is made of a non-shielding material and the back sheet 5 is made of a shielding material. It should be understood, however, that variations of this embodiment are also contemplated by the present invention. For example, the entire cover can be constructed of RF shielding material except for a window over the treatment zone (the treatment zone is characterized as the area above the applicator transmitting antenna). In an alternative embodiment, the entire cover, or a portion thereof, can be constructed of non-shielding material, with strips of shielding material adhered thereto. For example, RF shielding material perforated in concentric circles, or other shapes, are bonded

to the outer surface of the transparent material. In such embodiments, the window over the treatment zone can be variable in size, with the user able to peel off certain shielding strips to match the transmission region to that of the wound to be treated. Other variations are also considered within the scope of the present invention.

5 In preferred embodiments, proper placement of the cover 1 over the applicator is required for the device to operate. Preferably, the applicator (such as the one disclosed in the present applicants' earlier patent application) incorporates RF shielding material as a capacitor which is part of the electronic tuning of the applicator. Without the cover, the applicator cannot be tuned, thus the electromagnetic energy treatment device will detect a fault and will not operate. In one embodiment, as shown in FIG. 2, cover 1 includes a shielded side which conveys a particular capacitance upon the circuitry enclosed within the applicator. When the requisite capacitance is present, the applicator sends an appropriate voltage signal to a previously described power generator device (described in earlier application filed by inventors), enabling the device. In the absence of the cover conveying the requisite capacitance, the voltage signal remains outside of a predetermined range and the power generating device is disabled. In other words, the RF shielding provided by the cover acts as an additional source of capacitance (Y) which changes the final capacitance of system (Z). The RF generating system is adjusted such that it is only operable when the capacitance is within the range provided by the capacitance within the internal applicator pad shield circuitry (X) plus the capacitance (Y) provided by the cover.

The present invention is operated by placing the treatment applicator into the cover through its open end, with the treatment side of the applicator oriented towards the front sheet

and the coaxial cable of the applicator protruding through the open end. A permanent adhesive peel strip (which is located on the tab portion or the back sheet) is removed, exposing the adhesive. Tab portion is folded over the end of the applicator, with the semi-circular cutout notch aligned with the coaxial cable. The tab portion is then pressed against
5 the back sheet to fully close the cover.

Where the cover includes an extended tab portion, there is no semi-circular cable cutout. Rather the extended tab portion is folded over and wrapped around the coaxial cable and bonded together to form a biohazard barrier. For further securement, a portion of the tab portion also adheres to the back sheet.

Next, the peel strip material is removed from the outer surface of the front sheet to expose a low bonding force adhesive. The covered applicator is aligned with the wound site. Indicia, such as printed designs, may be located on the outer surface of the front sheet for facilitating proper alignment. The cover is then adhered to the bandaged wound site, thus ensuring proper location of the applicator to the wound site. The adhesive is not permanent
15 and can easily be pulled away from the bandaged site.

Following treatment, the cover is removed from the applicator and properly disposed. Preferably, removal of the cover involves the following steps. First, the cover is gripped at the two corners away from the end with the protruding coaxial cable. Pulling the corners in opposite directions causes the cover to tear at the center. As the tear clears the cover can be
20 removed from the applicator and disposed. For embodiments including the extended tab portion, the user continues the tear the cover past the intersection of the applicator and cable until the cover can be removed.

From the foregoing, it will be appreciated by those skilled in the art that the present invention provides a particularly effective and advantageous method of and apparatus for overcoming many of the limitations associated with the treatment of patients using electromagnetic energy. It will also be readily appreciated by one with ordinary skill in the art to use the method and apparatus of the present invention in other applications, such as veterinary applications.

Although certain presently preferred embodiments of the present invention have been specifically described herein, it will be apparent to those skilled in the art to which the invention pertains that variations and modifications of the various embodiments shown and described herein may be made without departing from the spirit and scope of the invention.

CLAIMS

We claim:

1. An apparatus for covering a treatment applicator comprising a cover having a front surface, a back surface, and at least one open end, wherein at least a portion of said cover is

5 constructed of an RF shielding material.

2. Apparatus according to claim 1, wherein said back surface of said cover is constructed of said RF shielding material.

3. Apparatus according to claim 2, wherein at least a portion of said front surface of said cover is constructed of said RF shielding material.

4. Apparatus according to claim 1, wherein said RF shielding material is metallized polyethylene.

5. Apparatus according to claim 1, further comprising at least one adhesive strip located on said front surface.

6. Apparatus according to claim 1, further comprising means for closing said open
15 end of said cover.

7. Apparatus according to claim 6, wherein said closing means further comprises a tab extending from said front surface and means for securing said tab to said back surface.

8. Apparatus according to claim 7, wherein said securing means is selected from the group consisting of adhesive, mating fasteners and mating ZIP-LOCK® strips.

20 9. Apparatus according to claim 7, wherein said tab has an opening located therein.

10. Apparatus according to claim 9, wherein said opening is a semi-circular notch.

11. Apparatus according to claim 7, further comprising perforations located along said tab.

12. Apparatus according to claim 6, wherein said closing means further comprises a
5 tab extending from said back surface and means for securing said tab to said front surface.

13. Apparatus according to claim 6, wherein said closing means further comprises a
first tab extending from said front surface, a second tab extending from said back surface, and
means for securing said first tab to said second tab.

14. Apparatus according to claim 1, wherein said cover is waterproof and bacterial
resistant.

15. An apparatus for covering a treatment applicator comprising a cover having a front
surface, a back surface, at least one open end, and at least one strip of RF shielding material
removable connected to said cover.

16. Apparatus according to claim 15, wherein said front surface is made of a non-
15 shielding material, wherein said at least one strip overlies said front surface, and wherein said
at least one strip further comprises a perforated strip.

17. Apparatus according to claim 15, wherein said at least one strip is removably
adhered to the front surface.

18. Apparatus according to claim 15, wherein said at least one strip further comprises
20 multiple strips, each adhered to the front surface of the cover and separably removable

19. An electromagnetic treatment apparatus comprising an RF generating system, a cover, and an applicator connected to said RF generating system and located within said cover, wherein said cover further comprises RF shielding that conveys a capacitance upon circuitry in said applicator.

sf-956038

COVER FOR ELECTROMAGNETIC TREATMENT APPLICATOR

Abstract of the Disclosure

A disposable cover for electromagnetic treatment applicators prevents undesired
 5 exposure to potentially harmful radiation. The cover is a pouch-like structure having a back
 surface (which faces opposite, or away from, the treatment area) constructed from shielding
 material, such as metallized polyethylene. At least a portion of the cover which faces the
 treatment area is constructed solely from non-shielding material. Securing means, such as
 adhesive strips, ZIP-LOCK®, or other interlocking edges, secure the applicator inside the
 10 cover and close off any leaks. The electromagnetic properties of the cover are integrated into
 the circuitry for the treatment applicator, such that the applicator is not functional in the
 absence of the cover. In use, an electromagnetic treatment applicator is inserted into the
 cover and positioned over the area to be treated, with the non-shielding, or “window”, portion
 of the cover overlying the treatment area. Once assembled, the applicator/cover combination
 15 forms a closely matched and tuned network for effecting a highly efficient RF output. When
 activated, the generated electromagnetic energy only exits the cover through the opening or
 “window”, thereby preventing exposure of the patient or caregiver to potentially harmful
 radiation.

20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

FIG 1






Fig. 2



Capacitance from internal shield (X) + Capacitance from cover shield (Y) = Final system capacitance (Z)

004163 TOST 3360

FIG 3



Regensis Biome 1435 N. Hayden Road, Sco	
Approvals	Date
Drawn Art Loya	04/14/99
Checked M. D. L.	4/16/99
Released	
CPI Model 4201 Treat Disposable Co	

DECLARATION FOR UTILITY PATENT APPLICATION

AS A BELOW-NAMED INVENTOR, I HEREBY DECLARE THAT:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: COVER FOR ELECTROMAGNETIC TREATMENT APPLICATOR, the specification of which is attached hereto unless the following box is checked:

- ☐ was filed on * as United States Application Serial No. or PCT International Application No. * and was amended on * (if applicable).

I HEREBY STATE THAT I HAVE REVIEWED AND UNDERSTAND THE CONTENTS OF THE ABOVE-IDENTIFIED SPECIFICATION, INCLUDING THE CLAIMS, AS AMENDED BY ANY AMENDMENT REFERRED TO ABOVE.

I acknowledge the duty to disclose information which is material to the patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

Application No.	Country	Date of Filing (day/month/year)	Priority Claimed?
			<input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

Application Serial No.	Filing Date
60/154,435	17 September 1999

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Application Serial No.	Filing Date	Status
		<input type="checkbox"/> Patented <input type="checkbox"/> Pending <input type="checkbox"/> Abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under § 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Date _____ Name: Frank R. GEORGE
Residence: Scottsdale, Arizona
Citizenship: United States
Post Office Address: 10187 E. San Salvadore Drive, Scottsdale, Arizona 85258

Date _____ Name: Robert T. BRYANT
Residence: Tempe, Arizona
Citizenship: United States
Post Office Address: #154, Tempe, Arizona 85281

Date _____ Name: Michael F. DALY
Residence: Phoenix, Arizona
Citizenship: United States
Post Office Address: 6814 North First Place, Phoenix, Arizona 85012

Date _____ Name: Arthur A. LOYA
Residence: Mesa, Arizona
Citizenship: United States
Post Office Address: 510 S. Extension, No. 1037, Mesa, Arizona 85210

Date _____ Name: Mary C. RITZ
Residence: Scottsdale, Arizona
Citizenship: United States
Post Office Address: 10187 E. San Salvadore Drive, Scottsdale, Arizona 85258